BOXER[®] 322D BY MORBARK[®]

Model Specifications

Model Features

1/4" thick (6 mm)

Independent Track

Drive Controls

Engine System	US	Metric
Engine	Kubota	
Cooling System	Liquid	
Horsepower	22.0 HP	16.4 kW
Fuel Type	Diesel	
Fuel Capacity	4.5 Gallons	17 Litres
Hydraulic Capacity	16 Gallons	60.6 Litres
Hydraulic Flow (Combined)	12.4 GPM	47 LPM
Hydraulic Flow (Aux)	9.4 GPM	35.6 LPM
Hydraulic Flow (Drive)	3.0 GPM	11.4 LPM
System Pressure	3000 PSI	20684 kPa
Engine Warranty	2 years	
Product Warranty	1 year	

Units	US	Metric
Track Gauge	27.5 in	699 mm
Track Width	7 in	180 mm
Weight (No Attachment)	1900 lbs	862 kg
Length (No Attachment)	68 in	1727 mm
Length (w/Bucket)	93 in	2362 mm
Width (Overall)	34.5 in	876 mm
Height (Boom Lowered)	49 in	1245 mm
Height (Boom Raised)	92 in	2337 mm
Hinge Pin Height (Fully Raised)	70 in	1778 mm
Dump Height	54 in	1372 mm
Dump Angle	34 °	
Reach	28 in	711 mm
Tip Capacity	1325 lbs	601 kg
Operating Capacity, 35% of tip load.	464 lbs	210 kg
Ground Clearance	5 in	127 mm
Ground Speed (Max)	3.4 mph	5.5 km/h
Ground Pressure	4.24 PSI	29.2 kPa



1/2" Thick (13 mm)

Boom Arms

www.boxerequipment.com | 800.831.0042 | PO Box 1000 | Winn, MI 48896