BOXER[®] 600HD

Model Specifications

Model Features

Engine System	US	Metric
Туре	Kubota	
Cooling System	Liquid	
HP/kW	24.8 HP	18.5 kW
Fuel Type	Diesel	
Fuel Capacity	4.5 Gallons	17.1 Litres
Hydraulic Capacity	16 Gallons	60.6 Litres
System Flow (Total)	22 GPM	83 L/min
Hydraulic Flow Aux (Hi)	11.3 GPM	43 L/min
Hydraulic Flow (Drive)	10.7 GPM	41 L/min
System Pressure	3000 PSI	20684 kPa
Engine Warranty	2 years, 2,000 Hours	
Product Warranty	1 year, 1,000 Hours	

Units	US	Metric
Track Gauge	27 in	686 mm
Track Width	7 in	180 mm
Weight (no attachment)	2380 lbs	1078 kg
Length (w/out Bucket)	73.375 in	1864 mm
Length (w/Bucket)	96 in	2438 mm
Width (Overall)	34.675 in	881 mm
Height (Overall)	52.675 in	1338 mm
Height (Fully Raised)	98 in	2489 mm
Operating Capacity (35%)	617 lbs	280 kg
Tip Capacity	1763 lbs	799 kg
Hinge Pin Height (Fully Raised)	74 in	1880 mm
Dump Height	56 in	1422 mm
Dump Angle	37 Degrees	
Ground Clearance	5 inches	127 mm
Ground Speed (Fwd/Rev)	4.3/3.1 MPH	7.0/5.0 km/h
Ground Pressure	5.36 PSI	37 kPa

Hydraulic Oil Cooler **Piloted Joystick** Controls (2) 2" (50 mm) Bore-welded Lift Cylinders Dual Hydrostatic Hydraulic System Operator Hip Padding 21⁄2" (64 mm) Bore-welded Tilt Cylinder Kubota D902, 600 ³/₄" Thick (19 mm) 2-Button 24.8-HP (18.5 kW) Boom Arms Pressure **Diesel Engine** Relief Block ALLER AL Front Tie-down Points Rear Tie-down Points Universal Attachment Plate 7" (180 mm) Low-Impact Tracks Tri-lobe Mid-wheels Serviceable Front Idlers Updated 2/23/17

www.boxerequipment.com | 800.831.0042 | PO Box 1000 | Winn, MI 48896