



MORBARK

► Beever 1415 ◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER

📞 **1300 072 926** | globalmachinerysales.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
E sales@globalmachinerysales.com.au
F (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148
E sales@globalmachinerysales.com.au
F (02) 8678 2478



MORBARK BEEVER 1415



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all Morbark equipment, the 1415 is a long-lasting, durable machine backed by a world-class parts and service support team.




Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 14" high throat opening allows for easy feeding of branchy material and reduced saw labour.



Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 4,911 kg/m of combined material pulling force.



360° Hydraulic Chute

Full 360° hydraulic chute with swivel discharge and adjustable height puts chips right where they're needed without removing the Beever from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Chipping capacity 14" (35.56 cm)
 Engine CAT Diesel
 Horsepower 114 HP
 Height 256.5 cm
 Width 180.3 cm
 Length 469.9 cm
 Weight (approximate) 2,494.8 kgs
 Suspension heavy duty leafspring
 Infeed opening 60" wide x 31" high
 Throat opening 15" wide x 14" high
 Drum 14.5" wide x 21.375" diameter
 Fuel capacity 92.7 litres
 Hydraulic capacity 64.4 litres
 Frame 3.72 kgs, 15.24 cm channel
 Brakes Electric with breakaway
 Tyres (2) 235/80R16"
 Hitch 63.5 mm Pintle Ring

Equipment Highlights

14.5" wide x 21.375" diameter staggered-knife pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system.
 Top and bottom horizontal feed wheels equipped with serrated teeth and knife bars.
 Reversing automatic feed system.
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment.
 Fuel tank sight gauge, drain plug and shutoff valve.
 Hydraulic tank shut-off valve, drain plug and clean-out cover.
 Live hydraulics; ball valve, pump, motor and control valve.
 7.6 cm x 12.7 cm tubular steel telescoping drawbar with two 30.5 cm extensions.

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

Options Include

ChipSafe® Operator Safety Shield
 Folding Infeed Tray
 Winch package: heavy-duty, 2,268 kgs pull capacity with rope and 305cm chafe guard
 Custom paint and logo packages
 Hydraulic Swivel Discharge
 Cone Holder
 Flow Control
 Axle Options Available
 Fender Options Available
 Battery Box Options Available



MORBARK



1300 072 926 | globalmachinerysales.com.au